METHOD FOR PRODUCING A POLYMERIC MATERIAL POWDER AND DEVICE FOR CARRYING OUT SAID METHOD (VARIANTS)

Publication number: RU2173634 Publication date: 2001-09-20

Inventor: Applicant:

Classification:

- International:

B02C19/18; B02C19/22; B29B13/00; B29B13/10; B29B17/04; B02C19/00; B29B13/00; B29B13/10; B29B17/04; (IPC1-7): B29B13/00; B02C18/44;

B02C19/22, B29B17/00

- European:


B29B13/10; B29B17/00C2 Application number: RU20000122139 20000823 Priority number(s): RU20000122139 20000823 Also published as:

凤 WO0216099 (A1)

Report a data error here

Abstract not available for RU2173634 Abstract of corresponding document: WO0216099

The inventive method for producing a polymeric material powder consists in compressing said material by shearing the material during a pressure increase and cooling. Consecutive breakdown is carried out by shearing the material during the pressure decrease and cooling, and also during flashing at a rate ranging from 3x10<-3> to 1x10<-1> m/sec. into a medium having a pressure ranging from 0.01 to 0.15 MPa. The inventive device comprises a cylindrical body (1) provided with a loading and unloading orifices (2,3). A packing chamber (4) provided with compressing means (6, 15) arranged therein and a chopper chamber (5) provided with a rotatable reducing element arranged therein are successively mounted inside the body (1). Said reducing element represents a flap valve (10) embodied in the form of a disc or a taped cone, or in the form of a disc and a taped cone which are coaxially assembled. In the second embodiment, the reducing element represents a flap valve (16) embodied in the form of a collar arranged on the inner surface of the body (1). The inventive device is provided with means for cooling the shell of the packing chamber (4) and /or means (12) for cooling the compressing means, and also with means for cooling the reducing element (11) and/or means for cooling the shell of the chopper chamber (5).



Data supplied from the esp@cenet database - Worldwide